

PTFE laminates



PTFE LAMINATES

PETON 0,15 - N°41

CLASS: ● TIGHTNESS ● FDA

Description: PTFE coated glass fiber fabric

Application: High chemical (wet) sealing layer with medium mechanical strength

Weight (g/m ²)	300	% PTFE	64
Thickness (mm)	0,14	Tensile strength (N/cm)	290 x 290
Temperature (°C)	260	Color	Brown

PTFE LAMINATES

PETON 0,25 - N°42

CLASS: ● TIGHTNESS ● FDA

Description: PTFE coated glass fiber fabric

Application: High chemical (wet) sealing layer with medium mechanical strength

Weight (g/m ²)	470	% PTFE	57
Thickness (mm)	0,22	Tensile strength (N/cm)	520 x 410
Temperature (°C)	260	Color	Brown

PTFE LAMINATES

PETON 0,35 - N°43

CLASS: ● TIGHTNESS ● FDA

Description: PTFE coated glass fiber fabric

Application: High chemical (wet) sealing layer with medium mechanical strength

Weight (g/m ²)	630	% PTFE	54
Thickness (mm)	0,31	Tensile strength (N/cm)	660 x 510
Temperature (°C)	260	Color	Brown

PTFE LAMINATES

PETON ORANGE - N°35

CLASS: ● TIGHTNESS

Description: PTFE coated glass fiber fabric

Application: Acid indicator on valves and flange cover

Weight (g/m ²)	530	% PTFE	54
Thickness (mm)	0,40	Tensile strength (N/cm)	660 x 510
Temperature (°C)	260	Color	Orange

PTFE LAMINATES

PETON I AS - N°87

CLASS: ● TIGHTNESS ● ATEX

Description: Antistatic PTFE coated glass fiber fabric

Application: Sealing and antistatic layer

Weight (g/m ²)	700	% PTFE	50
Thickness (mm)	0,34	Tensile strength (N/cm)	600 x 420
Temperature (°C)	260	Color	Black

PTFE LAMINATES

PETON II AS - N°88

CLASS: ● TIGHTNESS ● ATEX

Description: Antistatic PTFE coated glass fiber fabric

Application: Sealing and antistatic layer

Weight (g/m ²)	470	% PTFE	50
Thickness (mm)	0,22	Tensile strength (N/cm)	520 x 410
Temperature (°C)	260	Color	Black